



## Straight male stud connectors



Technical data			Dimensions	
Item no.	Pressure range [bar (psi)]	Operating temperature [°C (°F)]	Ø D [mm]	G
30.000	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	4	M5
30.001	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	4	M6
30.002	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	4	R1/8
30.003	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	4	R1/4
30.004	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	6	M5
30.005	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	6	M6
30.006	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	6	R1/8
30.007	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	6	R1/4
30.008	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	6	R3/8
30.009	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	8	R1/8
30.010	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	8	R1/4
30.011	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	8	R3/8
30.012	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	10	R1/8
30.013	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	10	R1/4
30.014	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	10	R3/8
30.015	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	10	R1/2
30.016	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	12	R1/4
30.017	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	12	R3/8
30.018	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	12	R1/2
30.019	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	16	R3/8
30.020	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	16	R1/2
30.002-G	-0.95 - 15 (-13.8 - 217.6)	-20 - 80 (-4 - 176)	4	G1/8
30.003-G	-0.95 - 15 (-13.8 - 217.6)	-20 - 80 (-4 - 176)	4	G1/4
30.006-G	-0.95 - 15 (-13.8 - 217.6)	-20 - 80 (-4 - 176)	6	G1/8
30.007-G	-0.95 - 15 (-13.8 - 217.6)	-20 - 80 (-4 - 176)	6	G1/4
30.008-G	-0.95 - 15 (-13.8 - 217.6)	-20 - 80 (-4 - 176)	6	G3/8
30.011-G	-0.95 - 15 (-13.8 - 217.6)	-20 - 80 (-4 - 176)	8	G3/8
30.012-G	-0.95 - 15 (-13.8 - 217.6)	-20 - 80 (-4 - 176)	10	G1/8
30.014-G	-0.95 - 15 (-13.8 - 217.6)	-20 - 80 (-4 - 176)	10	G3/8
30.015-G	-0.95 - 15 (-13.8 - 217.6)	-20 - 80 (-4 - 176)	10	G1/2
30.016-G	-0.95 - 15 (-13.8 - 217.6)	-20 - 80 (-4 - 176)	12	G1/4
30.017-G	-0.95 - 15 (-13.8 - 217.6)	-20 - 80 (-4 - 176)	12	G3/8
30.018-G	-0.95 - 15 (-13.8 - 217.6)	-20 - 80 (-4 - 176)	12	G1/2
30.019-G	-0.95 - 15 (-13.8 - 217.6)	-20 - 80 (-4 - 176)	16	G3/8
30.020-G	-0.95 - 15 (-13.8 - 217.6)	-20 - 80 (-4 - 176)	16	G1/2