



Connector cables M8, M12, 2 to 5-pin, material PUR



Product notes

- > Electric connection of vacuum switches, sensors or ejectors
- > Weather- and abrasion-resistant

Technical data

Item no.	Contact	Plug design	Cable length [mm]	Suitable for
20.503	Socket M8, 3-pin, open cable	Straight	2,000	Connection of sensors and sensor grippers
20.504	Plug M8, 3-pin 90°, socket M8, 3-pin	90° elbow	300	Connection of sensors and sensor grippers
20.507	Socket M8, 3-pin, open cable	90° elbow	2,000	Connection of sensors and sensor grippers
20.570	Plug M8, 3-pin, socket M8, 3-pin	Straight	1,500	Connection of sensors and sensor grippers
20.501	Socket M8, 4-pin, open cable	Straight	5,000	Connection of vacuum switches or compact ejectors
20.502	Plug M8, 4-pin, open cable	90° elbow	5,000	Connection of vacuum switches or compact ejectors
20.518	Socket M12, 4-pin, open cable	Straight	2,000	Connection of vacuum switches or compact ejectors
20.519	Socket M12, 4-pin, open cable	90° elbow	2,000	Connection of vacuum switches or compact ejectors
20.508	Socket M12, 5-pin, open cable	Straight	2,000	Connection of compact ejectors
20.509	Socket M12, 5-pin, open cable	90° elbow	2,000	Connection of compact ejectors
20.550	Special plug, 2-pin, open cable	Straight	1,500	Connection of base ejectors with blow-off boost EBA.08H.2-A