




Connectors | Tubing

Flexible vacuum and pressure tubing made from PUR blue transparent

Flexible vacuum and pressure tubing made from PUR blue transparent

SUITABLE FOR INSTALLATION IN DRAG CHAINS



Product notes

- > High flexibility enables small bending curve to build compact tubing systems
- > Suitable for air and tap water
- > Cut marks at 500 mm intervals facilitate installation
- > High chemical and mechanical resistance
- > Very high oil resistance
- > Rule of thumb for installation in drag chain: bending radius = 10 x outer diameter of tubing

Technical data

Item no.	Outer diameter [mm]	Inner diameter [mm]	Minimum bending radius [mm]	Pressure range [bar (psi)]	Operating pressure 20 °C (68 °F) [bar (psi)]	Usage temperature [°C (°F)]	Weight [g/m]	Packing unit [m]
61.090	3	2	8	-1 - 8 (-14.5 - 116)	29 (420.6)	-15 - 60 (5 - 140)	7	20
61.091	4	2.5	10	-1 - 8 (-14.5 - 116)	29 (420.6)	-15 - 60 (5 - 140)	9	20
61.092	6	4	15	-1 - 8 (-14.5 - 116)	29 (420.6)	-15 - 60 (5 - 140)	19	20
61.093	8	5	15	-1 - 8 (-14.5 - 116)	29 (420.6)	-15 - 60 (5 - 140)	36	20
61.094	10	6.5	20	-1 - 8 (-14.5 - 116)	29 (420.6)	-15 - 60 (5 - 140)	54	20