



Flexible vacuum and pressure tubing made of blue PUR

SUITABLE FOR INSTALLATION IN DRAG CHAINS

### Product notes

- > High flexibility enables small bending curve to build compact tubing systems
- > Suitable for air and tap water
- > Cut marks at 500 mm intervals facilitate installation

### Notes

- > Rule of thumb for installation in drag chain: Bending radius = 10 x outer diameter of tubing

### Ordering notes

- > Standard length 20 meters, color blue
- > Available in various tubing lengths and a wide selection of colors (black, red, orange, ochre, yellow, green, blue, light blue, transparent, pure white)
- > 61.062 standard color is black
- > Length of 50 meters generally only available in black

### Technical data

Item no.	Outer diameter [mm]	Inner diameter [mm]	Minimum bending radius [mm]	Pressure range [bar (psi)]	Operating pressure 20 °C (68 °F) [bar (psi)]	Usage temperature [°C (°F)]	Weight [g/m]	Packing unit [m]
61.056	3	2	8	-1 - 8 (-14.5 - 116)	29 (420.6)	-15 - 60 (5 - 140)	7	20 / 50 / 100
61.057	4	2.5	10	-1 - 8 (-14.5 - 116)	29 (420.6)	-15 - 60 (5 - 140)	9	20 / 50 / 100
61.058	6	4	15	-1 - 8 (-14.5 - 116)	29 (420.6)	-15 - 60 (5 - 140)	19	20 / 50 / 100
61.059	8	5	15	-1 - 8 (-14.5 - 116)	29 (420.6)	-15 - 60 (5 - 140)	36	20 / 50 / 100
61.060	10	6.5	20	-1 - 8 (-14.5 - 116)	29 (420.6)	-15 - 60 (5 - 140)	54	20 / 50 / 100
61.061	12	8	30	-1 - 8 (-14.5 - 116)	29 (420.6)	-15 - 60 (5 - 140)	74	20 / 50 / 100
61.062	16	11	60	-1 - 8 (-14.5 - 116)	29 (420.6)	-15 - 60 (5 - 140)	128	20 / 50 / 100