



Vacuum tubing made of highly flexible transparent PVC, reinforced with wire spiral



Product notes

- > Vacuum applications up to 95 %
- > Very smooth inner surface for residue-free transport of materials such as granulate
- > Suitable for continuous movement
- > High abrasion-proof

Technical data

Item no.	Outer diameter [mm]	Inner diameter [mm]	Minimum bending radius [mm]	Pressure range [bar (psi)]	Usage temperature [°C (°F)]	Weight [g/m]	Packing unit [m]
61.160	13	8	32	-0.9 - 16 (-13.1 - 232.1)	-5 - 65 (23 - 149)	140	1
61.161	16	10	20	-0.9 - 0 (-13.1 - 0)	-5 - 65 (23 - 149)	155	1
61.162	18	12	25	-0.9 - 0 (-13.1 - 0)	-5 - 65 (23 - 149)	180	1
61.163	20	14	30	-0.9 - 0 (-13.1 - 0)	-5 - 65 (23 - 149)	200	1
61.164	22	16	35	-0.95 - 8 (-13.8 - 116)	-5 - 65 (23 - 149)	225	1
61.165	24	18	40	-0.9 - 0 (-13.1 - 0)	-5 - 65 (23 - 149)	280	1
61.166	27	20	50	-0.9 - 0 (-13.1 - 0)	-5 - 65 (23 - 149)	340	1
61.167	33	25	60	-0.9 - 0 (-13.1 - 0)	-5 - 65 (23 - 149)	510	1
61.168	42	32	75	-0.9 - 0 (-13.1 - 0)	-5 - 65 (23 - 149)	730	1
61.169	53	40	100	-0.95 - 7 (-13.8 - 101.5)	-5 - 65 (23 - 149)	1,220	1