



Spiral tubing made of black PUR for vacuum and pressure applications



Product notes

- > Space-saving tubing for mobile vacuum or pressure systems without straining the connections
- > Suitable for pneumatic tools

Technical data

Item no.	Pressure range [bar (psi)]	Operating pressure 20 °C (68 °F) [bar (psi)]	Usage temperature [°C (°F)]
61.100	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.101	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.102	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.103	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.104	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.105	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.106	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.107	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.108	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.109	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.110	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.135	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.111	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.112	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.113	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.114	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.115	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.116	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.117	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.118	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.119	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.120	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.121	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.122	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.123	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)

Dimensions

A [mm]	Ø d [mm]	Ø D [mm]	L [mm]
70	3	16	210
150	3	16	450
230	3	16	700
390	3	16	1,200
120	4	24	360
180	4	24	540
350	4	24	1,100
480	4	24	1,500
700	4	24	2,100
1,040	4	24	3,200
1,450	4	24	4,400
90	6	30	270
160	6	30	500
230	6	30	700
430	6	30	1,300
620	6	30	1,900
910	6	30	2,800
1,300	6	30	3,900
1,850	6	30	5,600
250	8	42	750
390	8	42	1,200
540	8	42	1,700
770	8	42	2,400
1,045	8	42	3,200
1,550	8	42	4,700



Connectors | Tubing

Spiral tubing made of black PUR for vacuum and pressure applications

Technical data

Item no.	Pressure range [bar (psi)]	Operating pressure 20 °C (68 °F) [bar (psi)]	Usage temperature [°C (°F)]
61.124	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.125	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.126	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.127	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.128	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.129	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.130	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.131	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.132	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)
61.133	-1 - 7 (-14.5 - 101.5)	29 (420.6)	-15 - 60 (5 - 140)

Dimensions

A [mm]	∅ d [mm]	∅ D [mm]	L [mm]
330	10	58	1,000
470	10	58	1,400
680	10	58	2,100
970	10	58	3,000
1,380	10	58	4,200
310	12	72	1,000
450	12	72	1,400
660	12	72	2,000
920	12	72	2,800
1,320	12	72	4,000

Dimensions

