



Straight tube reducers



Technical data

Item no.	Pressure range [bar (psi)]	Operating temperature [°C (°F)]
30.075	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.076	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.077	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.078	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.080	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)

Dimensions

Ø D1 [mm]	Ø D2 [mm]
6	4
8	6
10	8
12	10
16	12

Male stud connectors with ball bearing

Ball bearing enables applications with fast rotation or pivoting



Technical data

Item no.	Max. revolutions [1/min.]	Pressure range [bar (psi)]	Operating temperature [°C (°F)]
30.800	500	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.801	500	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.802	500	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.803	500	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.804	500	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.805	500	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.806	400	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.807	400	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.808	400	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.809	300	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.810	300	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.811	300	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.812	300	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.813	250	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.814	250	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)
30.815	250	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)

Dimensions

Ø D [mm]	G
4	M5
4	M6
4	R1/8
6	M6
6	R1/8
6	R1/4
8	R1/8
8	R1/4
8	R3/8
10	R1/8
10	R1/4
10	R3/8
10	R1/2
12	R1/4
12	R3/8
12	R1/2