



Cartridge male stud connectors, round, hex key



Technical data			Dimensions	
Item no.	Pressure range [bar (psi)]	Operating temperature [°C (°F)]	Ø D [mm]	G
30.200	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	4	M5
30.201	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	4	M6
30.202	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	4	R1/8
30.203	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	6	M5
30.204	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	6	M6
30.205	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	6	R1/8
30.206	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	6	R1/4
30.207	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	8	R1/8
30.208	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	8	R1/4
30.209	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	8	R3/8
30.210	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	10	R1/4
30.211	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	10	R3/8
30.212	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	10	R1/2
30.213	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	12	R3/8
30.214	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	12	R1/2

Straight male stud connectors with cut-off valve

Locking of compressed air or vacuum during disassembly, release after reconnection



Technical data			Dimensions		
Item no.	Effective passage area [mm ²]	Pressure range [bar (psi)]	Operating temperature [°C (°F)]	Ø D [mm]	G
30.761	1.6	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	4	M5
30.762	2	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	4	R1/8
30.763	2.3	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	6	M5
30.764	7.3	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	6	R1/8
30.765	7.3	-0.95 - 15 (-13.8 - 217.6)	0 - 60 (32 - 140)	6	R1/4